

Room Name | Bay - Handwashing, Type B

Room Number: BHWS-B

Last modified | 01/03/2016
Briefed Area | 1.00
Remarks
Occupancy | 1
Hours of Operation | 24 Hours
Acoustics
Description / Special Requirements

An area off the corridor, which may be a recessed bay, with handwashing facilities for staff to cleanse their hands before and after every patient contact. Type B refers to a Medium Handbasin with elbow action lever taps - for procedural handwashing; taps may be basin mounted or wall mounted. A vanity unit is optional.

Room Fabrics

AusHFG code	Description	Material	Finish	Specification	Comments
1045	Floor finish	Vinyl, non slip	Textured	Seamless, coved	under basin
3000	Wall finish	Paint	Acrylic, washable		
3060	Wall finish	Vinyl	Prefinished	Splashback	Default = vinyl: tiles also acceptable
4031	Wall protection	Composite	Prefinished PVC	Corner guards to 1500 AFFL	as required, equal to 'Acrovyn'
5010	Ceiling - Plasterboard	Plasterboard	Paint, washable	Flush set, suspended	
6030	Cornice	Aluminium	Powdercoat	24mm shadow angle	
2000	Skirting	Vinyl	Prefinished	Floor vinyl coved, 150 mmH	

Fittings and Furniture

AusHFG code	Description	Group	Qty	Comments
FF-530	Basin vanity top	1	1	optional
FF-6152	Dispenser - disposable glove	2	1	optional
FF-6154	Dispenser - paper/ hand towel	2	1	
FF-6156	Dispenser - soap	2	1	
FF-6158	Dispenser - soap antiseptic	2	1	optional
FF-5824	Waste bin - general	3	1	

Fixtures, Equipment and associated Services

AusHFG code	Description	Grp	Qty	Ele	Data	CdW	HtW	WmW	Tap	Dns	Gas	Comments
FE-2800	Basin - handwash, Type B	1	1	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	elbow action lever taps, basin or wall mounted

Service Requirements

AusHFG code	Description	Comments
S-5000	Airconditioning	
S-6000	General fluorescent	

Services

Room Name | Bay - Handwashing, Type B

Room Number: BHWS-B

AusHFG code	Description	Group	Qty	Comments
S-5000	Airconditioning	1	1	
S-6000	General fluorescent	1	1	