

Room Name	Corridor - Patient Treatment Areas		Room Number CORR
Revision	5		
Issue Date	28.06.2021		
BRIEFING			
Briefed Area	0.00 m ²		
Hours of Operation	24 hours		
Occupancy			
Acoustics			
Remarks			
Description / Special Requirements	<p>The Corridor - Patient Treatment Areas indicates requirements for circulation spaces between patient treatment spaces, patient accommodation and clinical support spaces within departments.</p> <p>Corridor widths will vary between departments and will depend on the requirement for frequent bed transportation; widths must allow for the safe movement and passing of trolleys, beds, wheelchairs and other mobile equipment as required. Provision should be made for situations where oversized additional equipment, e.g. bed extensions or bariatric beds, are in use.</p> <p>Guidance for the calculation of areas (m2) for corridors is provided for in Health Planning Unit Schedules of Accommodation as circulation percentages.</p> <p>Refer to AusHFG Part C: Design for Access, Mobility, Safety and Security for further information.</p> <p>Additional Design Considerations:</p> <ul style="list-style-type: none"> • Wall protection is recommended to protect wall linings and finishes from damage from impact. The height of the wall protection will be dependent on equipment frequently moved through the space; a height range of 900mm minimum up to 1500mm is recommended depending on service requirements. • Handrails are to be provided along not less than one side of all corridors in patient care areas to provide assistance and support for patients and visitors. Handrails are to be continuous along the corridors wherever practical. • Cleaner's electrical outlets to be provided at regular intervals as per mandatory requirements. • Corridor lighting, where patients are transported on beds/trolleys, should be positioned to prevent unnecessary glare to patient eyes. Light fittings shall be recessed, flush fitting and sealed to prevent dust ingress. • Manual controls to power-operated doors shall be located on the continuous accessible path of travel no closer than 500 mm from an internal corner and between 1000 mm to 2000 mm from the hinged door leaf in any position as per the requirements of AS1428.1. 		
SERVICES			
Electrical	BODY PROTECTED	<input type="checkbox"/>	CARDIAC PROTECTED <input type="checkbox"/>
HVAC	AIRCONDITIONING	<input checked="" type="checkbox"/>	AIRCONDITIONING: hepa filtered <input type="checkbox"/>
	AIRCONDITIONING: positive pressure	<input type="checkbox"/>	AIRCONDITIONING: negative pressure <input type="checkbox"/>
	EXHAUST: room exhaust	<input type="checkbox"/>	VENTILATION <input type="checkbox"/>
Lighting	LIGHTING: colour corrected	<input type="checkbox"/>	LIGHTING: dimmable <input type="checkbox"/>
	LIGHTING: downlights	<input type="checkbox"/>	LIGHTING: downlights, dimmable <input type="checkbox"/>
	LIGHTING: fluorescent/LED, downlights	<input type="checkbox"/>	LIGHTING: fluorescent/LED, flush with ceiling, tamper proof <input type="checkbox"/>
	LIGHTING: fluorescent/LED, general	<input checked="" type="checkbox"/>	LIGHTING: indirect <input type="checkbox"/>
Security / Nurse Call	NURSE CALL SYSTEM	<input checked="" type="checkbox"/>	

Room Fabrics

AusHFG code	Description	Comment
CLTI-002	CEILING: acoustic, drop-in tiles, 600 x 1200	
CLCN-009	CORNICE: wall trim fixing	

Room Name | Corridor - Patient Treatment Areas

Room Number CORR

AusHFG code	Description	Comment
FLVY-007	FLOOR FINISH: vinyl, seamless, coved, standard slip resistant	
FIRT-010	HANDRAIL	provided to at least one side of the corridor, to be continuous wherever practical; may be combined with crash rail if provided
FLSK-010	SKIRTING: vinyl, floor vinyl coved, 150H, prefinished	
WLWA-004	WALL FINISH: paint, acrylic, washable	
WLPR-006	WALL PROTECTION: corner guards	coordinated with adjacent wall protection
WLPR-026	WALL PROTECTION: rigid wall sheeting	height dependent on service requirements, crash rails are also acceptable

Fittings, Furniture and Equipment (FF&E) Items

AusHFG code	Description	Group	Qty	Comment
FIDI-001	DISPENSER: alcohol based hand rub	2	1	quantity to suit layout and infection control policies

Engineering Services

AusHFG code	Description	Group	Qty	Comment
ITCL-001	ANNUNCIATOR: nurse call	1	1	ceiling mounted; quantity to suit layout and service requirements
ELGP-110	GPO: single, wall mounted, cleaner	1	1	quantity and location to comply with mandatory requirements.